### **AAC PARTITION PANELS**





AIRCRETE EUROPE | PRODUCT PORTFOLIO



## **PANELS**PARTITION PANELS



Aircrete Partition Panels are a superior building solution for all internal applications such as separation walls, corridors or storage rooms in residential and commercial constructions.

The **entire non-load bearing** structure of your building can be developed with a single product which allows **reliable** and **efficient construction** for contractors.

The attractive **SUPER SMOOTH** surface results in an easy and cost effective finish. After skimming the joints, the wall is directly ready for wallppering and/or painting.

- Standard length from 2.4 to 3 meters
- Easy drilling, sawing and nailing
- Time and cost efficient installation
- SUPER SMOOTH surface



#### **SUPER SMOOTH FINISH**


Aircrete Partition Panels have a unique SUPER SMOOTH surface due to the most innovative European production technology. A double wired high-speed cutter closes the aerated concrete pores leaving an exceptionally smooth surface on both sides of the panel. Developers will experience the advantage of significant savings in building time and finishing cost while the installation workers will have a much easier job in finishing the walls.

# **PANELS**PARTITION PANELS



### **DIMENSIONS AND TECHNICAL SPECIFICATIONS**

	DENSITY	
	A-600	A-800
THICKNESS (mm):	70 - 150	70 - 150
LENGTH (mm):	≤3000	≤3000
HEIGHT (mm):	600 - 750	600 - 750
AVERAGE COMPRESSIVE STRENGTH:	4,8 MPa	5,6 MPa
THERMAL CONDUCTIVITY (λ-LAMBDA):	0,16 W/mK	0,22 W/mK
SHRINKAGE DUE TO DRYING:	Does not exceed 0.20 mm/m	
DRY MASS:	580 kg/m³	720 kg/m³
DESIGN WEIGHT INCL. REINFORCEMENT:	680 kg/m³	820 kg/m³
FRANSPORT WEIGHT INCL. REINFORCEMENT:	780 kg/m³	920 kg/m³









Aircrete Europe Münsterstraat 10 7575 ED Oldenzaal The Netherlands

Tel: +31 (0) 541 571020 Email: info@aircrete.com www.aircrete.com